

Sports Flooring System

DYNAMIK Flexi-Beam Elite

Sprung Timber Sports Floor



DYNAMIK
The Sports Surfacing Specialist

Official Provider



The DYNAMIK Flexi-Beam Elite system is a cradle and beam sprung area elastic sports floor. It incorporates Flexi-Beams which support a 22mm premium engineered sports board. The system can be packed and levelled to take out variations in the sub floor.


The structure of the Flexi-Beam Elite system incorporates Flexi-Beams to provide a stable base for the 22mm board and allows for underfloor heating and insulation to be incorporated between the beams. Given it can be packed and levelled off a structural slab, the requirement for a levelling screed is avoided.

Flexi-Beam Elite Benefits

- Meets the requirements of EN 14904
- Sport England compliant
- Packed & levelled construction
- Underfloor heating compatible
- Complies with the latest ESFA specification
- Factory finished sports lacquer
- 25 year warranty
- Enhanced acoustic properties

Surface Finishes


The Flexi-Beam Elite engineered sports board is available in four different wood species:




European Oak



Beech



Ash



Canadian Maple

Official Partners



DYNAMIK Flexi-Beam Elite

Technical Specifications



DYNAMIK
The Sports Surfacing Specialist

Official Provider



1	Premium Engineered Sports Board	22mm
2	Flexi-Beam	36mm
3	Sports Cradle: 100mm x 100mm x 20mm	20mm
4	Levelling Shims	To Suit Void
System Thickness (excluding levelling shims)		78mm

A minimum void (drop in screed) of 88mm is required to install, pack and level the system.

Thickness of cradles/beams can vary dependent on void depth up to 100mm. For a greater void than 100mm, cradle-base packers can be used.

Performance Characteristics

Certification - EN14904	Class A4
Shock Absorption	55% < 75%
Vertical Deformation	2.3mm < 5.0mm
Rolling Load	≥1,500 N
Ball Rebound	≥ 90%
Slip Resistance	80 - 110

Specification Downloads



Product Specification downloads for our DYNAMIK products are available through NBS Source.

Visit Us



Product specifications may be subject to change without notice, please contact DYNAMIK for the latest product information

Sports Flooring

Acoustic Walling

Track & Gym

Maintenance & Protection

0117 3015120 - info@dynamiksport.co.uk - www.dynamiksportsfloors.co.uk

v.280921