

DYNAMIK Internal Sports Wall

Solid & Perforated Panels



The DYNAMIK Internal Sports Walling panels are both durable, cost effective and provide a highly decorative solution for busy sports hall environments. With high scratch and impact resistance and certified for sport, the panels are designed to be an integral component of the internal wall construction and can be fitted from floor to soffit. Solid panels can be combined with matching or contrasting Class A perforated (acoustic) panels to provide a continuous, flush wall finish.

Principle Features

Durability & Impact Resistance – Provides superior impact resistance from balls, equipment and hall users. This allows for both solid and acoustic panels to be used in a variety of layouts.

Time & Cost Savings – The panels are installed directly to studwork, thus eliminating the need for block work and other wet trades, providing a fast and efficient installation.

Factory Finished – Every panel is factory finished with a low maintenance, UV resistant, durable surface that does not require re-finishing over the life of the product.


Secret Clip Fixings – The secret clips allow for a seamless finish. They also provide a consistent spacing between adjoining boards.

Fire Performance – The panels are fire rated to comply with Building Regulations, Sport England and the Department for Education - Education & Skills Funding Agency (ESFA) requirements.

Colours - The panels are available in a range of colours & wood effects to provide a modern appearance that complements the sports floor and can achieve the required Light Reflectance Values (LRVs).

** Minimum order quantity 50m²*

Perforated (acoustic) panel



Solid panel



Technical & Performance Specifications - Solid & Perforated (Acoustic)

Panel Face	Factory finished, available in a range of colours & wood effect finishes (bespoke colours available upon request)
Fire Performance	Fire rated to European Class B-s1,d0
Panel Sizes (l x w x d)	Solid: 2400mm x 1200mm x 18mm / 2400mm x 592mm x 18mm - Standard sizes Perforated: 2400mm x 1200mm x 18mm / 2400mm x 592mm x 18mm (bespoke sizes available)
Compliance	Building Regulations, ESFA & Sport England compliant
Panel Weight	Solid panels: 40.60kg / 19.92kg Perforated panels: 38.72kg / 18.96kg
Acoustic Performance	Class A - Perforated panels (50x50mm batten system) Class B - Perforated panels (25x50mm batten system)

Specification Downloads



Product Specification downloads for our DYNAMIK products are available through NBS Source.

Visit Us



Product specifications may be subject to change without notice, please contact DYNAMIK for the latest product information