

GT15 Recycled Rubber Gym Tiles**TECHNICAL SPECIFICATION**

High Performance, Environmentally Friendly, Rubber Crumb Gym Tiles

Commercial, professional and home gyms

Guaranteed for 5 years (Manufacturers limited warranty)

Product Reference	GT15
Thickness	15mm
Dimensions	1000mm x 1000mm
Tolerances	Width / Length +/- 0.4% Thickness +/- 1mm
Dimensional Stability	+0.242% 2 Hours 60°C -0.092% 48 Hours 20°C 65% Relative Humidity
Composition	Fine Granulated SBR Rubber with 15% EPDM Coloured Flecks
Profile	Flat Base - Bevel Edge
Density	950 kg/m ³
Nominal Weight	14.25 kg/m ²
Material	SBR Granules / Recycled Tyre Rubber
Bonding Agent	Polyurethane
Tear Strength EN13893	≥ 40kN/m Nominal
Temperature Stability	-30°C to +80°C
Fire Class EN13501	E-fl
Impact Sound	20dB Δ Lw Coupled with InstaFloor acoustic subfloor 30dB Δ Lw Nominal
VOC Emissions	A Rating – Very Low Emissions
Material Safety	PASS to EN71-3 & REACH Entry 28 Annex XVII
Quality Control	ISO9002 Quality Management
Recycled Content	Approx 85% Recycled SBR Rubber

Installation Process:

Tiles can be loose laid when installed within a closed perimeter. Option to bond to subfloor with F Ball F74 (2mm x 6mm trowel) or Mapei VS90 PLUS adhesive or other equivalent adhesives suitable for rubber flooring.

See Installation instructions for full details.

Guarantee covers manufacturing defects but does not include wear and tear.

This guarantee is subject to Dynamik Sport Surfaces Ltd standard terms and conditions.