

SP30 Shock Pad Recycled Rubber**TECHNICAL SPECIFICATION****High Performance, Environmentally Friendly, Rubber Strand Underlayment****Commercial and home gyms****Guaranteed for 5 years (Manufacturers limited warranty)**

Product Reference	SP30
Thickness	30mm
Dimensions	1000mm x 1000mm
Tolerances	Width / Length +/- 0.4% Thickness +/- 1mm
Dimensional Stability	+0.242% 2 Hours 60°C -0.092% 48 Hours 20°C 65% Relative Humidity
Composition	Strand SBR Rubber
Profile	Flat Base - Bevel Edge
Density	500 kg/m ³
Nominal Weight	15 kg/m ²
Material	Strand SBR / Recycled Tyre Rubber
Bonding Agent	Polyurethane
Tear Strength EN13893	≥ 40kN/m Nominal
Temperature Stability	-30°C to +80°C
Fire Class EN13501	E-fl
Impact Sound	23dB Δ Lw Coupled with GT40 40mm Rubber Tile
VOC Emissions	A Rating – Very Low Emissions
Material Safety	PASS to EN71-3 & REACH Entry 28 Annex XVII
Quality Control	ISO9002 Quality Management
Recycled Content	Approx 85% Recycled SBR Rubber

