



Floor Covering: Milan magnetically backed LVT

Thickness: 3mm

Plank: 228mm x 1219mm

Midi Plank: 152mm x 914mm

Tile: 457mm x 914mm

Colour Range: 9 Wood effect colours available in plank and 3 stone effect colours in tile formats.

Underlay: Ezy-Install 25 dual grip technology magnetically receptive acoustic underlay.

Roll size: 2.9mm x 0.98m x 5m

System Thickness: 5.9mm (includes LVT floor finish).

))) **17dB** - Reduction of Impact Sound

InstaGroup are committed to circularity in the flooring market and have developed a range of magnetically backed LVT products. Installation on our Ezy-Install magnetically receptive acoustic rubber underlay creates a fully adhesive free flooring solution allowing the reuse of flooring to support circularity. Clients are searching for flooring solutions that do not contaminate building assets, and allowing repurposing of spaces without the use of further raw materials to repair the structure in readiness for new floor finishes.

The Milan LVT range is manufactured using a heated high pressure system ensuring high quality, durability and dimensional stability.

System Benefits

- **Adhesive Free** – making circular flooring solutions easy, no adhesive contamination to both the floor covering or the subfloor.
- **Quick, clean installation** – can be installed over an existing floor and walked on immediately.
- **All-round performance** – excellent impact sound reduction, provides vapour barrier for moisture mitigation and is hygienic, naturally anti-microbial and anti-allergy.
- **Sustainable and recyclable** – manufactured using recycled rubber, with no contaminating glues so that flooring can be easily lifted and recycled.
- **Easy floor maintenance** – worn or damaged tiles can be quickly replaced, avoiding costly or inconvenient downtime.
- **Design Agility** – easy repurposing of areas, enhancing customer experience in fitness, retail and hospitality applications

MILAN LVT

LVT Key features

- Formaldehyde emission: Class E1 (EN 717-1)
- Dimensional stability: < 0.10% (EN 434 / EN ISO 23999)
- Performance classification 33-42 (EN 685-43 / EN ISO 26986)
- Installed on Ezy-Install dual grip magnetically receptive acoustic underlay

LVT Technical specifications


- Product type: Heterogeneous PVC floor coverings (EN 649)
- Wear layer: 0.55mm / Group T (EN 660-2)
- Reaction to fire: Class Bfl-S1 (EN 13501-1)
- Slip resistance: Class DS (EN 13893) R9-R10** (DIN 51130)

** Depending on embossing

Colour Range




Iced Oak




Sand Oak




Silver Pine




Washed Pine




Aged Oak



Vintage Elm



Old Larch



Oak



Silver Wenge



Zinc



Grey Cloud



Grey Cement