



Ultra resistant protective floor coverings rolls. A cost-effective solution to protect your floor from foot traffic and light weights:

1. Transparent wear layer
2. Decorated compact non-woven impregnation
3. Calendered sheet + single glass veil reinforcement

Properties	Standards	Touchdown
------------	-----------	-----------

Declaration of Performance

0120-013-DoP-2021-02

Classification

Type of flooring	EN ISO 10582	Compact vinyl floorcoverings
------------------	--------------	------------------------------

Technical Characteristics

Total thickness	EN ISO 24346	1.45 mm
Total weight	EN ISO 23997	2.2 kg/m ²
Width	EN ISO 24341	2 m
Length	EN ISO 24341	27lm

Technical Performances

Static indentation	EN ISO 24343-1	0.10 mm
Dimensional stability	EN ISO 23999	<0.1%
Reaction to fire	EN 13501-1	Bfl-s1*
Impact noise reduction	EN ISO 717-2	$\Delta L_w = 2 \text{ dB}$
Electrical properties	EN 1081	$R_1 > 10^9 \text{ ohms}$
Antistatic properties	EN 1815	<2kV
Formaldehyde	-	No formaldehyde
Pentachlorophenol	-	No pentachlorophenol

Accessories

An unroller is available for the installation of Touchdown:

Device composed of 2 supporting frameworks outfitted with castors and one mandrel.

Unroller for Touchdown:

