



40mm Recycled Rubber Gym Tiles

Technical Specification

High Performance, Environmentally Friendly, Rubber Strand Underlayment for the use in commercial, professional and home gyms.

Guaranteed for 5 years (Manufacturers limited warranty).

Product Reference	ECO-Flex40
Thickness	40mm
Dimensions	1000mm x 1000mm
Tolerances	Width / Length +/- 0.4%
Thickness	+/- 1mm
Dimensional Stability	+0.242% 2 Hours 60oC -0.092% 48 Hours 20oC 65% Relative Humidity
Composition	Fine Granulated SBR Rubber
Profile	Flat Base - Bevel Edge
Density	950 kg/m ³
Nominal Weight	38 kg/m ²
Material	SBR Granules / Recycled Tyre Rubber
Bonding Agent	Polyurethane
Tear Strength EN13893	≥ 40kN/m Nominal
Temperature Stability	-30°C to +80°C
Fire Class EN13501	E-fl
Impact Sound	23dB Δ Lw Nominal Coupled with acoustic subfloor 33dB Δ Lw - Nominal
VOC Emissions	A Rating – Very Low Emissions
Material Safety	PASS to EN71-3 & REACH Entry 28 Annex XVII
Quality Control	ISO9002 Quality Management ISO14001 Environmental
Recycled Content	1 Tile (1m ²)) Recycles 5 Car Tyres / 0.8 Truck Tyres - Nominal

Installation Process:

Tiles can be loose laid when installed within a closed perimeter. Option to bond to subfloor with F Ball F74 (2mm x 6mm trowel) or Mapei VS90 PLUS adhesive or other equivalent adhesives suitable for rubber flooring.

See Installation instructions for full details.

Guarantee covers manufacturing defects but does not include wear and tear.

This guarantee is subject to Dynamik Sport Surfaces Ltd standard terms and conditions

**Product specifications may be subject to change without notice, please contact DYNAMIK for the latest product information*